



### **PERFORMANCE**

Manage your projects with ease thanks to an intuitive design and advanced printing capabilities

- A3 mid-to-low-volume colour devices with two speeds.
- Large 10.1 inch WSVGA full colour touch screen designed for a user-friendly experience and intuitive operating feel
- Vivid and vibrant colour delivers a crisp, even finish.
- Optional space-saving Inner Finisher incorporates Eco Staple, Staple, and Staple On-demand functionalities.
- My ADVANCE functions allow users to create their own personalised experience, tailored to meet their unique needs.



## COST CONTROL

#### Streamline workflows while managing costs

- Forced Job Hold reduces paper and toner wastage.
- Ability to change print settings at the device allows for extra control over jobs.
- Blank page removal comes standard and works to reduce paper wastage.
- Track usage and control your costs utilising Canon's uniFLOW Online Express free software.



## **INTEGRATION**

#### Seamlessly integrate with key line-ofbusiness systems

- Seamlessly integrate with key line-ofbusiness systems to power your digital transformation journey.
- Personalised workflows give users the ability to take control of the way they want to manage their information so that it works best for them.
- Scan to myself and Google Drive<sup>™</sup> plus other popular cloud destinations to enhance workflow efficiencies\*.



## **SECURITY**

#### Advanced standard security feature set to help safeguard sensitive information and assist in regulatory compliance

- Security Information and Event Management (SIEM) system integration helps provide real-time insights into potential threats to the network and printers.
- Ensure data is secure with HDD encryption.
- Technology to verify that the device boot process, firmware, and applications initialise without alterations or tampering.



## **MOBILITY**

#### Workers and contractors can achieve ultimate freedom and flexibility with Expanded Mobile OS Support

- Mobile workflows are set up with built in WiFi and mobile applications to easily allow users to connect, print, scan and capture using Canon PRINT Business.
- Full support for Apple® Airprint® and Android™ Mopria™ Mobile Printing.
- Simple and easy mobile connectivity with in-built WiFi plus options to connect through Bluetooth and Near Field Communication (NFC).



## **SUSTAINABILITY**

## Designed to help achieve environmental goals

- Motion sensors and sleep recovery triggers work to reduce unnecessary power consumption.
- Bio-based plastics are used throughout the machine for an environmentally friendly approach to printing performance.

<sup>\*</sup> Requires uniFLOW Online Express or uniFLOW Online subscription.

### **DEVICE SECURITY**

The imageRUNNER ADVANCE DX C3700i Series feature the ability to help verify that the device boot process, firmware, and applications initialise at startup, without any alterations or tampering by malicious third parties.

During operation, McAfee Embedded Control™ utilises a whitelist to protect against malware and tampering of firmware and applications.\*\*



### **CONFIGURATION**

\*\* These features are available on third generation imageRUNNER ADVANCE Gen III Series III or imageRUNNER ADVANCE DX models only. McAfee Embedded Control™ requires Unified Firmware Platform v3.9 or above.



#### **Booklet Finisher**

- 2-tray, 3,250 sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Booklet-making up to 20 sheets and nonstaple saddle folded capacity up to 3 sheets (A3/A4R)
- Supports Eco stapling 4 sheets (80 gsm) and Staple On-demand 50 sheets (80 gsm)
- Supports optional internal 2/3 and 2/4 hole inner punchers



#### Staple Finisher

- 2-tray, 3,250 sheet capacity
- Corner and double stapling up to 50 sheets (80 gsm)
- Supports Eco stapling 4 sheets (80 gsm) and Staple On-demand
- 50 sheets (80 gsm)
- Supports optional internal and 4 hole inner punchers



# **imagerunner advance DX C3700i** SPECIFICATIONS



Main Unit		Scan Specifications	
Туре	A3 Colour Laser Multifunctional	Туре	Standard: Single Pass Duplexing Automatic Document Feeder* (2-sided to 2-side
Core Function	Print, Copy, Scan, Send, Store and Optional Fax		(Automatic with DADF)) * Detect Feeder Multi Sheet Feed is Supported.
Processor	1.75 GHz Dual Core Processor	Document Feeder	Up to 200 Sheets
Control Panel	10.1" TFT LCD WSVGA Colour Touch Panel	Paper Capacity (80 gsm)  Acceptable Originals and Weights	Platen: Sheet, Book, and 3-Dimensional Objects
Memory Hard Disk Drive	Standard: 3.0 GB RAM Standard*: 320 GB (Available Disk Space: 250 GB)	Acceptable Originals and Weights	Document Feeder Media Weight:
	Optional: 1 TB * A different initial HDD may be used.		1-sided Scanning: 38 to 220 gsm (BW, CL) 2-sided Scanning: 38 to 220 gsm (BW, CL) An acceptable weights of AGR or smaller is 50 to 220 gsm.
Interface Connection	Network: Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n) Optional: NFC, Bluetooth Low Energy Others:	Supported Media Sizes	Platen Max. Scanning Size: Up to 2970 x 431.8 mm Document Feeder Media Size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, B6R Custom Size: 70.0 x 139.7 mm to 304.8 x 431.8 mm
	Standard: USB 2.0 x1 (Host), USB 3.0 x1 (Host), USB 2.0 x1 (Device) Optional: Serial Interface, Copy Control Interface	Scan Speed (ipm: BW/CL, A4)	1-sided Scanning: 135/135 (300 x 300 dpi, Send), 51/51 (600 x 600 dpi, Copy) 2-sided Scanning: 270/270 (300 x 300 dpi, Send), 51/51 (600 x 600 dpi, Copy)
Paper Supply Capacity (A4, 80 gsm)	Standard: 1,200 Sheets 2 x 550-sheet Cassettes, 100-sheet Multi-purpose Tray Maximum: 2,300 Sheets (with Cassette Feeding Unit-API)	Scan Resolution (dpi)	Scan for Copy; $600 \times 600$ Scan for Send; (Push) $600 \times 600$ (SMB/FTP/WebDAV/IFAX), (Pull) $600 \times 600$ Scan for Fax: $600 \times 600$
Paper Output Capacity (A4, 80 gsm)	Standard: 250 Sheets Maximum: 3,450 Sheets (with Staple Finisher-AA1 or Booklet Finisher-AA1 and Copy Tray-J2)	Pull Scan Spec	Colour Network ScanGear2. For both TWAIN and WIA Supported OS: Windows® 7/8.1/10/Server 2008/Server 2008 R2/Server 2012/ Server 2012 R2/Server 2016
Finishing Capabilities	Standard: Collate, Group With Options: Collate, Group, Offset, Staple, Saddle Stitch, Hole Punch, Eco Staple, Staple On-demand	Scan Method	Push Scan, Pull Scan, Scan to Box, Scan to Advanced Box, Scan to Network, Sca to USB Memory Key, Scan to Mobile device, Scan to cloud (uniFLOW Online)
Supported Media Types	Multi-purpose Tray: Thin, Plain, Heavy*, Recycled, Coated*, Colour, Tracing, Bond,	Send Specifications	Chandradi F. and Maharran A.FA.V. (CMTD) CMD 2.0 FTD Web DAVAN-II Dav
	Transparency, Label, Pre-punched, Envelope * SRA3 is unsupported for Coated (257–300 gsm) and Heavy (257–300	Destination	Standard: E-mail/Internet FAX (SMTP) SMB 3.0 FTP WebDAV Mail Box Optional: Super G3 FAX, IP Fax
	gsm) paper. Upper Cassette: Thin, Plain, Heavy, Recycled, Colour, Bond, Transparency,	Address Book	LDAP (2,000)/Local (1,600)/Speed dial (200)
	Pre-punched, Envelopee Lower Cassette: Thin, Plain, Treavy, Recycled, Colour, Bolid, Iransparency, Pre-punched, Envelopee Lower Cassette: Thin, Plain, Heavy, Recycled, Colour, Bond, Transparency, Pre-punched, Envelopee	Send Resolution (dpi)	Push: Up to 600 x 600 Pull: Up to 600 x 600
	* Envelope Feeder Attachment A (standard) is required.	Communication Protocol	File: FTP (TCP/IP), SMB 3.0 (TCP/IP), WebDAV E-mail/I-Fax: SMTP, POP3
Supported Media Sizes	Multi-purpose Tray: Standard Size: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R Custom Size: 98.4 x 139.7 mm to 320.0 x 457.2 mm Free Size: 98.4 x 139.7 mm to 320.0 x 457.2 mm	File Format	Standard: TIFF, JPEG, PDF (Compact, Searchable, Apply policy, Optimise for Wet PDF/A-1b, Trace & Smooth, Encrypted, Device Signature, User Signature), XPS (Compact, Searchable, Device Signature, User Signature), Office Open XML (PowerPoint, Word)
	Envelopes: COMIO No.10, Monarch, DL, ISO-C5 Envelope Custom Size: 98.0 x 98.0 mm to 320.0 x 457.2 mm Upper Cassette: Standard Size: 44, A5, A5R, A6R, B5 Custom Size: 105.0 x 148.0 mm to 297.0 x 215.9 mm Envelopes: ISO-C5	Universal Send Features	Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Sender's Name (TTI), Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Originals
	Lower Cassette: Standard Size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R Custom Size: 105.0 x 148.0 mm to 304.8 x 457.2 mm	Fax Specifications Maximum Number of	2
	Envelopes*: COM10 No.10, Monarch, DL * Envelope Attachement A (standard) is required.	Connection Lines Modem Speed	Super G3: 33.6 kbps
Supported Media Weights	Multi-purpose Tray: 52 to 300 gsm* * SRA3 is Unsupported for Coated (257–300 gsm) and Heavy		G3: 14.4 kbps
	(257–300 gsm) Paper.	Compression Method	MH, MR, MMR, JBIG
	Upper/Lower Cassette: 52 to 220 gsm Duplex: 52 to 220 gsm	Resolution (dpi)	400 x 400 (Ultra Fine), 200 x 400 (Super Fine), 200 x 200 (Fine), 200 x 100 (Normal)
Warm-up Time	Quick Startup Mode: 4 seconds or less*  * Time from device power-on to when the copy icon appears and is enabled to operate on the touch panel display.  From Deep Sleep Mode: 10 seconds or less	Sending/Receiving Size	Sending: A3, A4, A4R, A5", A5R", B4, B5'², B5R" Receiving: A3, B4, A4, A4R, A5R, B5, B5R "1 Sent as A4 '2 Sent as B4 Short
	From Power On: 10 seconds or less*  * Time from device power on, until copy ready (not print reservation).	Fax Memory	Up to 30,000 Pages (2,000 Jobs)
Dimensions (W x D x H)	Standard (with Single Pass DADF): 565 x 722 x 887 mm	Speed Dials	Max. 200
Installation Space (W x D)	Basic: 978 x 1,118 mm (with Single Pass DADF + right cover open + Multi-purpose Tray Extension Extended + Paper Cassette Open) Fully Configured: 1,651 x 1,118 mm (with Single Pass DADF + Staple Finisher-AA1/	Group Dials/Destinations	Max. 199 Dials
		Sequential Broadcast	Max. 256 Addresses
	Booklet Finisher-AA1 + Copy Tray-J2 Extension Extended + Paper Cassette Open)	Memory Backup Fax Features	Yes  Sender's Name (TTI), Selecting the Telephone Line (when sending fax), Direct
Weight Print Specifications	Standard (with Single Pass DADF): Approx. 80.6 kg Including Toner	TaxTeddies	Send, Delayed Send, Preview, Job Done Notice, TX Report, Interrupt Transmission, Sequential Broadcasting, Password/Subaddress Sending, Confidential Mailbox, 2 on 1 Log
Print Speed (BW/CL)	iR-ADV DX C3730i: Up to 30 ppm (A4,A5,A5R,A6R), Up to 15 ppm (A3), Up to 20 ppm (A4R)	Store Specifications	
	iR-ADV DX C3720i: Up to 20 ppm (A4,A5,A5R,A6R), Up to 15 ppm (A3),	Mail Box (Number Supported)	100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes
Drint Decelution (dni)*	Up to 20 ppm (A4R) 600 x 600, 1200 x 1200 (Half-speed)	Advanced Box	Maximum 10,000 Pages (2,000 Jobs) Stored  Communication Protocol: SMB or WebDAV
Print Resolution (dpi)* *Laser Resolution			Supported Client PC: Windows® 8.1/10 Concurrent Connections (Max.): SMB: 64, WebDAV: 3
Page Description Languages	Standard: UFRII, PCL6 Optional: Adobe® PostScript® 3 <sup>TM</sup>	Advanced Box Available	Standard: 16 GB
Direct Print	Supported File Types: PDF, EPS, TIFF/JPEG and XPS	Disc Space Advanced Box Features	(With Option: Max. 480 GB)  Authentication for Advanced Box Log-in, Sort Function, Printing a PDF File with a
Printing from Mobile and Cloud	AirPrint®, Mopria®, Google Cloud Print®, Canon Business Print, and unIFLOW Online. A range of software and MEAP-based solutions are available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales	Security Specifications	Password, Search, File Preview, Authentication Management, Open to Public, URITX, Backup/Restore
	representative for further information.	Authentication and Access Control	Standard: User Authentication (Picure Login, Picture and PIN Login, Card Login,
Fonts	PCL Fonts: 93 Roman, 10 Bitmap Fonts, 2 OCR Fonts, Andalé Mono WT J/K/S/T*1 (Japanese, Korean, Simplified and Traditional Chinese), Barcode Fonts*2 PS fonts: 136 Roman *1 Requires Optional PCL International Font Set-A1 *2 Requires Optional Barcode Printing Kit-D1		Username and Password Login, Function Level Login, Mobile Login), Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online Express (PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN Login, Username and Password Login, Department ID and PIN Login, Function Level Login), Access Management System (Access Control)
Print Features	Secured Print, Secure Watermark, Header/Footer, Page Layout, Two-sided Printing, Mixed Paper Sizes/Orientations, Front/Back Covers, Toner Reduction, Poster Printing, Forced Hold Printing, Print Date, Scheduled Printing, Printing Using a Virtual Printer	Document Security	Print Security (Secure Print, Encrypted Secure Print, Forced Hold Printing, uniFLOW Secure Print*), Receive Data Security (Confidential Fax Inbox Forwarding Received Documents Automatically), Scan Security (Encrypted PDF, Device Signature PDF/KPS, User Signature PDF/KPS, Adobe LiveCvcle® Rights
Operating System As of July, 2019.	UFRII: Windows® 7/8.1/10/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016/Server 2019, Mac OS X (10.10 or later) PCL: Windows® 7/8.1/10/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016/Server 2019 R2/Server 2016/Server 2019 PS: Windows® 7/8.1/10/Server 2008 R2/Server 2018 R2/Server 2012/Server 2012 R2/		Management ES2.5 Integration), BOX Security (Mail Box Password Protected, Advanced Box Access Control), Send Data Security (Setting for Requesting Password Input Per Transmission, Restricted E-mail/File Send Functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support), Document Tracking (Secure Watermark) *1 Requires uniFLOW Online/uniFLOW.
	Server 2016/Server 2019, Mac OS X (10.10 or later) PPD: Windows® 7/8.1/10, Mac OS X (10.9 or later)	Network Security	TLS 1.3, IPSec, IEEE802.1X Authentication, SNMP V3.0, Firewall Functionality (IP/
Copy Specifications			MAC Address Filtering), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/Wired LAN), Disabling Unused Functions (Enabling/Disabling Protocols/
Copy Speed (BW and CL)	IR-ADV DX C37301: Up to 30 ppm (A4, A5, A5R, A6R), Up to 15 ppm (A3), Up to 20 ppm (A4R) IR-ADV DX C37201: Up to 20 ppm (A4, A5, A5R, A6R), Up to 15 ppm (A3), Up to 20 ppm (A4R)		Applications, Enabling/Disabling Remote UI, Enabling/Disabling \(\tilde{U}\)SB Interface), G3 FAX Separation from LAN, USB Port Separation from LAN, Prohibit the Execution of Files Stored in Advanced Box in the MFP, Scan and Send-virus Concerns for E-mail Reception
First-Copy-Out Time (A4, BW/CL)	Approx. 5.9/8.2 seconds or less	Device Security	Protecting HDD Data (HDD Data Encryption (FIPS140-2 Validated), HDD Data
Copy Resolution (dpi)	600 x 600		Overwrite Erase, HDD Lock), Standard HDD Initialise, Trusted Platform Module (TPM), Job Log Conceal Function, Protecting MFD Software Integrity, Checking
Multiple Copies	Up to 999 copies	Desides Many 1 11 11	MFD Software Integrity (Verify System at Startup, Runtime Intrusion Detection)
Copy Density Magnification	Automatic or Manual (9 Levels)  Variable Zoom: 25% to 400% (1% Increments)	Device Management and Auditing	Administrator Password, Digital Certificate And Key Management, Audit Log, Cooperating with External Security Audit System (Security Information and Even Management), Image Data Logging, Security Policy Setting
	Preset Reduction/Enlargement: 25%, 50%, 61%, 70%, 81%, 86%, 100% (1:1), 115%, 122%, 141%, 200%, 400%	Environmental Specifications	
Copy Features	Preset R/E Ratios by Area, Two-sided, Density Adjustment, Original Type	Operating Environment	Temperature: 10 to 30 °C
Cupy readiles	Selection, Interrupt Mode, Book to Two Pages, Two-sided Original, Job Build, N on 1, Add Cover, Insert Sheets, Different Size Originals, Page Numbering, Copy Set	Power Requirements	Humidity: 20 to 80 % RH (Relative Humidity) 220–240V, 50/60Hz, 4A
	Numbering, Sharpness, Erase Frame, Secure Watermark, Print Date, Gutter, Print & Check, Negative/Positive, Repeat Images, Mirror Image, Copy ID Card, Skip Blank Pages, Free Size Original, Colour Mode, Reserved Copy, Copy Sample	Power Consumption	Z2O-240V, 50/60Hz, 4A Maximum: 1,500 W Standby: Approx. 45.1 W*1 Sleep Mode: Approx. 0.8 W*2 † Reference Value: Measured One Unit.

Consumables	NDC C7Ts as DV/C/MAY
Toner	NPG-67 Toner BK/C/M/Y
Toner Yield (Estimated @5% Coverage)	NPG-67 Toner BK: 36,000 Pages NPG-67 Toner C/M/Y: 19,000 Pages
Software and Printer Mana	-
Tracking and Reporting	Universal Login Manager (ULM), uniFLOW Online Express
Remote Management Tools	eMaintenance, Content Delivery System
Scanning Software	Network ScanGear
Optimisation Tools	Canon Driver Configuration Tool, NetSpot Device Installer
Platform	MEAP (Multifunctional Embedded Application Platform)
Paper Supply Options	
Cassette Feeding Unit-AP1	Paper Capacity: 550 Sheets x 2 Cassettes (1,100 sheets) (80 gsm) Paper Type: Thin, Plain, Recycled, Colour, Heavy, Bond, Transparency, Pre-punched Paper Size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, Custom Size (105.0 x 148.0 mm to 304.8 x 457.2 mm) Paper Weights 52 to 220 gsm
	Power Source: From the Main Unit Dimensions (W $\times$ D $\times$ H): 565 $\times$ 615 $\times$ 248 mm Weight: Approx. 16.0 kg
Output Options	•
Copy Tray-J2	Capacity (with 80 gsm paper):
	A4, A5R, B5, B5R: 100 Sheets A3, A4R, B4: 75 Sheets Dimensions (W x D x H): 444 x 373 x 176 mm (attached to the main unit, when the extension tray is extended) Weight: 0.5 kg
Inner 2Way Tray-J1	Tray Capacity (with 80 gsm paper):  Upper Tray: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R, Custom Size (98 x 1 39.7 mm to 320.0 x 457.2 mm): 100 Sheets Lower Tray: A4, A5, A5R, A6R, B5, B5R: 250 Sheets SRA3, A3, A4R, B4, Custom Size (98.4 x 139.7 to 320.0 x 457.2 mm): 100 Sheets Paper Weight: 52 to 300 gsm Dimensions (W x D x H): 426 x 407 x 76 mm Weight: 0.7 kg
Inner Finisher-K1	Tray Capacity, (with 80gsm paper): Upper Tray:
Staple Finisher-AA1	Tray Capacity (with 80gsm paper): Upper Tray: A4, A5, A5R, A6R, B5: 250 sheets SRA3, A3, A4R, B4, B5E: 125 Sheets Lower Tray: A4, A5, A5R, B5: 3.000 Sheets SRA3, A3, A4R, B4, B5R: 1.500 Sheets SRA3, A3, A4R, B4, B5R: 1.500 Sheets A6R: 250 sheets Envelope: Monarch 30 sheets, COM10 No.10, DL, ISO-C5: 100 sheets Paper Weight: Upper Tray: 52 to 256 gsm Lower Tray: 52 to 300 gsm Staple Position: Corner, Double Staple Capacity: A4, B5: 50 sheets (52 to 90 gsm) A3, A4R, B4: 30 sheets (52 to 90 gsm) Eco Staple: A3, A4: 5 Sheets (52 to 64 gsm) 4 Sheets (65 to 81 4 gsm) 3 Sheets (62 to 105 gsm) Staple On-demand: 50 Sheets (90 gsm) Power Source: From the Main Unit Dimensions (W x D x H): 637 x 623 x 1,016 mm (when the extension tray is extended) Weight: A4prox. 3.00 kg

Booklet Finisher-AA1	(Includes the Staple Finisher-AAI basic staple specifications) Booklet Stitch Paper Size. A3, A4R, B4 Booklet Stitch Paper Size. A3, A4R, B4 Booklet Stitch Staple Capacity. 20 Sheets (52 to 81.4 gsm) x 10 sets (including 1 cover sheet up to 256 gsm) Non Staple Folded Bunch Capacity. 3 Sheets (52 to 105 gsm) Power Source: From the Main Unit Dimensions (W x D x H): 637 x 623 x 1,016 mm (when the extension tray is extended) Weight: Approx. 53.0 kg
2/3 Hole Puncher Unit-A1	(Requires either the Staple Finisher-AA1 or Booklet Finisher-AA1) Two or Three Holes Acceptable Punch Paper Weight: 52 to 300 gsm Acceptable Punch Paper Size: Two Holes: A3, A4, A4R, A5, B4, B5, B5R Three Holes: A3, A4, B4, B5 Power Source: From the Finisher
2/4 Hole Puncher Unit-A1	(Requires either the Staple Finisher-AA1 or Booklet Finisher-AA1) Two or Four Holes Acceptable Punch Paper Weight: 52 to 300 gsm Acceptable Punch Paper Size: Two Holes: A3, A4, A4R, A5, B4, B5, B5R Four Holes: A3, A4 Power Source: From the Finisher
Hardware Accessories	
Others	Utility Tray-B1
Security Options	
Data Security	2.5 inch/1TB HDD-P1
System and Controller Op	tions
Print Accessories	PS Printer Kit-BJ1, PCL International Font Set-A1
Barcode Printing	Barcode Printing Kit-D1
System Accessories	Copy Control Interface Kit-A1, Serial Interface Kit-K3, Connection Kit-A2 for Bluetooth LE, NFC Kit-E1
Fax Accessories	Super G3 FAX Board-AZ1, Super G3 2nd Line Fax Board-AU1, Remote Fax Kit-A1, IP FAX Expansion Kit-B1
Other Options	
Accessibility Accessories	ADF Access Handle-A1, Voice Guidance Kit-G1, Voice Operation Kit-D1
Consumables	Staple-P1, Staple Cartridge-Y1

For information and services contact

Canon Australia Pty Ltd Canon New Zealand Ltd 1800 444 199 0800 222 666

canon.com.au/business canon.co.nz/business





